



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA

TESAF

Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

workshop organized by the **Italian Society of Agricultural Engineering (AIIA)**



Book of abstracts

27 November 2020



<https://www.facebook.com/Associazione.Italiana.Ingegneria.Agraria>



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA

TESAF

Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Organization

Chairman

Paolo Tarolli, Dept. Land Environment Agriculture and Forestry (TESAF),
University of Padova, Italy

Scientific Board

Giacomo Scarascia Mugnozza, University of Bari, Italy (*President AIIA*)
Fabrizio Mazzetto, Free University of Bozen, Italy
Antonio Coppola, University of Basilicata, Italy
Patrizia Tassinari, University of Bologna, Italy

Panel Moderators

Paolo Tarolli, University of Padova, Italy
Fabrizio Mazzetto, Free University of Bozen, Italy
Giuseppe Modica, Università degli Studi Mediterranea Reggio Calabria, Italy
Claudio Gandolfi, University of Milan, Italy

Invited Speakers

Matthias Forkel, TU Dresden, Germany
Jean-Stephane Bailly, AgroParisTech, France
Xiangzhou Xu, Dalian University of Technology, PR China
Anette Eltner, TU Dresden, Germany
Niculita Mihai, Alexandru Ioan Cuza University of Iasi, Romania

Sponsored by Italian Association of Agricultural Engineering (AIIA) (<http://www.aiaa.it>)

The Italian Association of Agricultural Engineering (AIIA) was founded in 1959, as a national association, member of the Commission Internationale du Génie Rural (CIGR). IT coordinates and develops initiatives in the agricultural engineering field, that is those scientific and technical disciplines related to engineering works applied to the development of agricultural and forestry systems, facilitating the exchange of experiences and research results among the scholars in the field. AIIA promotes initiatives to facilitate the application of engineering principles to processes that drive territorial phenomena, with the aim to study, model, and enhance the biological systems for a sustainable development of agriculture, food production, land use, and environment.



Programme

- 09:00 *Welcome Chairman* **Paolo Tarolli**, University of Padova, Italy
- 09:05 *Welcome President AIIA* **Giacomo Scarascia Mugnozza**, University of Bari, Italy
- Panel 1 – Ecosystem (moderator Paolo Tarolli)**
- 09:10 *Earth observation, machine learning and ecosystem modelling for agricultural drought monitoring and impact prediction*
Matthias Forkel¹, **Laura Crocetti**², **Wouter Dorigo**¹, ¹TU Dresden, ²Vienna University of Technology
invited talk
- 09:25 *Landsat-based surface energy balance modelling of daily actual evapotranspiration in a Mediterranean ecosystem*
Hassan Awada, **Simone Di Prima**, **Sirca Costantino**, **Mario Pirastru**, University of Sassari, Italy
- 09:35 *A multi-platform approach to dissect the evapotranspiration response to drought of black poplar*
Flavia Tauro¹, **Antonino Maltese**², **Antoine Harfouche**¹, **Salvatore Grimaldi**¹, ¹University of Tuscia, ²University of Palermo, Italy
- 09:45 *Comparison of remote and ground sensing technologies to compute NDVI values of diseased and healthy grapevine*
Gabriele Daglio, **Damiano Zampieri**, **Raimondo Gallo**, **Fabrizio Mazzetto**
Free University of Bozen, Italy
- 09:55 > *discussion*
- Panel 2 – Vegetation & Landuse (moderator Fabrizio Mazzetto)**
- 10:15 *Monitoring from close-range remote sensing the hydraulic resistance (Manning) of agricultural channel network*
Jean-Stephane Bailly^{1,2}, **Fabrice Vinatie**¹, **Gabrielle Rudi**³, ¹LISAH Univ Montpellier, ²AgroParisTech, ³G-Eau Univ Montpellier, France *invited talk*
- 10:30 *Assessment of the riparian leaf density using different satellite imagery in a mountain stream*
Giovanni Romano, **Giovanni Francesco Ricci**, **Francesco Gentile**, University of Bari Aldo Moro, Italy
- 10:40 *Use of remotely sensed data for the evaluation of inter-row cover intensity in vineyards*
Francesco Palazzi¹, **Marcella Biddoccu**¹, **Enrico Borgogno Mondino**², **Eugenio Cavallo**¹, ¹National Research Council (CNR), ²University of Turin, Italy
- 10:50 *Comparison between two methodologies for the Individual Tree Height Estimation through a LiDAR mounted on a drone*
Monica F. Rinaldi, **Gabriele Daglio**, **Raimondo Gallo**, **Fabrizio Mazzetto**, Free University of Bozen–Bolzano, Italy
- 11:00 *Sentinel-1 SAR satellite data and open-source Python algorithms for unsupervised burned area detection in Mediterranean ecosystems*
Giandomenico De Luca¹, **João M.N. Silva**², **Giuseppe Modica**¹, ¹Università degli Studi Mediterranea di Reggio Calabria, Italy; ²University of Lisbon, Portugal
- 11:10 *LULC object-oriented classification in Google Earth Engine: an application in the Trasimeno Lake area*
Andrea Tassi, **Marco Vizzari**, University of Perugia, Italy
- 11:20 *Designing and implementing a multifunctional network of urban green infrastructures*
Stefano Chiappini¹, **Francesco Paci**¹, **Nicole Hofmann**¹, **Andrea Galli**¹, **Adriano Mancini**¹, **Ernesto Marcheggiani**^{1,2}, ¹Università Politecnica delle Marche, Italy; ²University of Leuven, Belgium
- 11:30 > *discussion*



- Panel 3 – Digital Terrain Analysis & Soil erosion (moderator Giuseppe Modica)**
- 11:50 *Topography meter: remote sensing with a novel 3D surface measuring technique*
Xiangzhou Xu, Dalian University of Technology, PR China *invited talk*
- 12:05 *Monitoring of vegetated agricultural terraces systems through SfM-TLS data fusion technique*
Sara Cucchiaro^{1,2}, **Daniel J. Fallu**³, **Antony G. Brown**³, **Paolo Tarolli**², ¹University of Udine,
²University of Padova, Italy; ³Tromso University Museum, Norway
- 12:15 *Soil erosion and SfM covering various spatio-temporal scales*
Anette Eltner, Technische Universität Dresden, Germany *invited talk*
- 12:30 *Assessing sediment dynamics and torrent control works efficiency in a debris-flow catchment using multi-temporal topographic surveys*
Federico Cazorzi¹, **Sara Cucchiaro**¹, **Lorenzo Marchi**², **Marco Cavalli**², ¹University of Udine,
²National Research Council CNR-IRPI, Italy
- 12:40 *Primary impacts and cascading processes of the Vaia storm in the Rio Cordon mountain catchment (Belluno Province)*
Lorenzo Martini¹, **Giacomo Pellegrini**¹, **Riccardo Rainato**¹, **Lorenzo Picco**^{1,2}, ¹University of Padova,
Italy; ²Universidad Austral de Chile, Chile
- 12:50 *UAV-SfM 4D mapping of landslides activated in steep terraced agricultural context*
Luca Mauri¹, **Eugenio Straffelini**¹, **Sara Cucchiaro**², **Paolo Tarolli**¹, ¹University of Padova,
²University of Udine, Italy
- 13:00 > *discussion & lunch break*
- Panel 4 – Water Resources Management (moderator Claudio Gandolfi)**
- 14:10 *Abandoned reservoirs and gully erosion analysis using LiDAR*
Niculita Mihai, Alexandru Ioan Cuza University of Iasi, Romania *invited talk*
- 14:25 *Remote Sensing advances in agricultural hydraulics and watershed protection*
Giulio Castelli, **Elena Bresci**, **Daniele Penna**, **Federico Preti**, University of Florence, Italy
- 14:35 *Analysis of time-series satellite images as a tool for planning river management strategies*
Paolo Fogliata, **Daniele Masseroni**, **Alessio Cislighi**, **Gian Battista Bischetti**, University of Milan,
Italy
- 14:45 *Early recognition of irrigated areas using Sentinel-2 data in Central Italy*
Lorenzo Vergni, **Marco Vizzari**, **Alessandra Vinci**, **Francesco Santaga**, **Francesca Todisco**,
University of Perugia, Italy
- 14:55 *Soil Moisture Retrievals from Unmanned Aerial Systems (UAS)*
Nunzio Romano¹, **Ruodan Zhuang**², **Salvatore Manfreda**¹, **Silvano Fortunato Dal Sasso**², **Carolina Allocca**¹, **Paolo Nasta**¹, ¹University of Naples Federico II, ²University of Basilicata, Italy
- 15:05 > *discussion*
- 15:25 *Conclusion* **Paolo Tarolli**, University of Padova, Italy



Summary

Matthias Forkel, Laura Crocetti, Wouter Dorigo

Earth observation, machine learning and ecosystem modelling for agricultural drought monitoring and impact prediction 7

Hassan Awada, Simone Di Prima, Sirca Costantino, Mario Pirastru

Landsat-based surface energy balance modelling of daily actual evapotranspiration in a Mediterranean ecosystem 8

Flavia Tauro, Antonino Maltese, Antoine Harfouche, Salvatore Grimaldi

A multi-platform approach to dissect the evapotranspiration response to drought of black poplar 9

Gabriele Daglio, Damiano Zampieri, Raimondo Gallo, Fabrizio Mazzetto

Comparison of remote and ground sensing technologies to compute NDVI values of diseased and healthy grapevine 10

Jean-Stéphane Bailly, Fabrice Vinatier, Gabrielle Rudi

Monitoring from close-range remote sensing the hydraulic resistance (Manning) of agricultural channel network 11

Giovanni Romano, Giovanni Francesco Ricci, Francesco Gentile

Assessment of the riparian leaf density using different satellite imagery in a mountain stream 13

Francesco Palazzi, Marcella Biddoccu, Enrico Borgogno Mondino, Eugenio Cavallo

Use of remotely sensed data for the evaluation of inter-row cover intensity in vineyards 14

Monica F. Rinaldi, Gabriele Daglio, Raimondo Gallo, Fabrizio Mazzetto

Comparison between two methodologies for the Individual Tree Height Estimation through a LiDAR mounted on a drone 15

Giandomenico De Luca, João M.N. Silva, Giuseppe Modica

Sentinel-1 SAR satellite data and open-source Python algorithms for unsupervised burned area detection in Mediterranean ecosystems 16

Andrea Tassi, Marco Vizzari

LULC object-oriented classification in Google Earth Engine: an application in the Trasimeno Lake area 17

Stefano Chiappini, Francesco Paci, Nicole Hofmann, Andrea Galli, Adriano Mancini, Ernesto Marcheggiani

Designing and implementing a multifunctional network of urban green infrastructures 18

Xiangzhou Xu

Topography meter: remote sensing with a novel 3D surface measuring technique 19

Sara Cucchiario, Daniel J. Fallu, Antony G. Brown, Paolo Tarolli

Monitoring of vegetated agricultural terraces systems through SfM-TLS data fusion technique 20

Anette Eltner

Soil erosion measurement across spatio-temporal scales 21



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA

TESAF

Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Federico Cazorzi, Sara Cucchiaro, Lorenzo Marchi, Marco Cavalli

Assessing sediment dynamics and torrent control works efficiency in a debris-flow catchment using multi-temporal topographic surveys 22

Lorenzo Martini, Giacomo Pellegrini, Riccardo Rainato, Lorenzo Picco

Primary impacts and cascading processes of the Vaia storm in the Rio Cordon mountain catchment (Belluno Province) 23

Luca Mauri, Eugenio Straffelini, Sara Cucchiaro, Paolo Tarolli

UAV-SfM 4D mapping of landslides activated in steep terraced agricultural context..... 24

Mihai Niculita

Abandoned reservoirs and gully erosion analysis using LiDAR 26

Giulio Castelli, Elena Bresci, Daniele Penna, Federico Preti

Remote Sensing advances in agricultural hydraulics and watershed protection..... 27

Paolo Fogliata, Daniele Masseroni, Alessio Cislighi, Gian Battista Bischetti

Analysis of time-series satellite images as a tool for planning river management strategies..... 28

Lorenzo Vergni, Marco Vizzari, Alessandra Vinci, Francesco Santaga, Francesca Todisco

Early recognition of irrigated areas using Sentinel-2 data in Central Italy..... 29

Nunzio Romano, Ruodan Zhuang, Salvatore Manfreda, Silvano Fortunato Dal Sasso, Carolina Allocca, Paolo Nasta

Soil Moisture Retrievals from Unmanned Aerial Systems (UAS)..... 30



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Panel 1 – Ecosystem

Reference topic: remote sensing, drought monitoring, agricultural drought

Presentation type: oral (invited talk)

Earth observation, machine learning and ecosystem modelling for agricultural drought monitoring and impact prediction

Matthias Forkel^{1*}, Laura Crocetti², Wouter Dorigo²

¹*Institute for Photogrammetry and Remote Sensing, Department of Geosciences, TU Dresden, Helmholtzstr. 10, 01069 Dresden, Germany (corresponding: matthias.forkel@tu-dresden.de)*

²*Department of Geodesy and Geoinformation, Vienna University of Technology, Wiedner Hauptstraße 8, 1040 Vienna, Austria*

Drought can cause severe impacts on agriculture in terms of reduced plant productivity and consequently yield losses. Climate warming, changes in evapotranspiration and precipitation can likely cause more frequent and more intense drought events. Remote sensing allows to monitor the development of drought events and to potentially estimate drought impacts on agriculture [1]. Here, we will first give an overview about recent developments in the satellite-based monitoring of agricultural droughts including soil moisture and vegetation state and about existing operational products and services. Secondly, we will outline the advantages and disadvantages of different approaches and describe the need to develop reliable systems to forecast potential impacts of drought on plant productivity and agricultural yield at monthly to seasonal scales. Thereby, machine learning approaches show a great potential to understand environmental controls and to predict plant productivity but they are highly depending on the quantity and quality of the underlying data. On the other hand, process-based environmental models are comprehensive and consistent tools that can be applied for environmental prediction but they rely on the built-in ecophysiological knowledge. We propose to integrate Earth observation with machine learning and environmental models in order to better understand environmental controls on plant productivity and to more reliably predict drought impacts on agriculture.

References

1. Laura Crocetti, Matthias Forkel, (...), Wouter Dorigo, 2020, Earth Observation for Agricultural Drought Monitoring in the Pannonian Basin (southeastern Europe): current state and future directions. *Regional Environmental Change*, accepted.



Reference topic: Remote sensing, Surface energy balance, actual evapotranspiration
Presentation type: oral

Landsat-based surface energy balance modelling of daily actual evapotranspiration in a Mediterranean ecosystem

Hassan Awada*, Simone Di Prima, Sirca Costantino, Mario Pirastru

Dept. of Agraria, University of Sassari, Viale Italia 39, 07100 Sassari, Italy. (corresponding: hawada@uniss.it)

Quantifying Evapotranspiration (ET) over natural vegetation is crucial in evaluating water status of ecosystems. Remote sensing-based surface energy balance models have been used extensively for estimating ET_a in agro-environments, however the application of these models to natural ecosystems is still limited. The surface energy balance algorithm for land (SEBAL) physical-based surface energy balance model was applied to estimate the actual evapotranspiration (ET_a) over Mediterranean maquis in a natural reserve in Sardinia island, Italy. The model was applied on thirty Landsat 5 and 8 images from 2009 to 2014 and results were compared to the data of a micrometeorological station with eddy covariance flux measurements. Comparing the SEBAL-based evaporative fraction (Λ_S) to the corresponding tower-derived evaporative fraction (Λ_T) indicates good fluxes estimations at Landsat overpass time ($R^2=0.83$, $RMSE=0.07$ and $MAE=0.05$). The upscaling factor Λ_S was used to upscale instantaneous latent heat flux (λE) to daily actual evapotranspiration ($ET_{a,24}$) under the hypothesis of diurnal self-preservation. Compared to ground based measured daily actual ET, the up-scaled $ET_{a,24}$ on average overestimated the measured daily evapotranspiration by nearly 21%. The model estimations of daily actual ET were satisfactory taking into consideration the high variable ground cover and the inherent variability of the biome composition, which can't be properly represented in the Landsat moderate spatial resolution. In this study we tested the potential of SEBAL model application in a natural ecosystem. This modelling approach will be used to represent the spatial dynamics of ET, that will be integrated into further environmental and hydrological applications.

References

1. Awada, H., Ciraolo, G., Maltese, A., Provenzano, G., Hidalgo, M. A. M., & Còrcoles, J. I. (2019). Assessing the performance of a large-scale irrigation system by estimations of actual evapotranspiration obtained by Landsat satellite images resampled with cubic convolution. *International Journal of Applied Earth Observation and Geoinformation*, 75, 96-105.
2. Maltese, A., Awada, H., Capodici, F., Ciraolo, G., La Loggia, G., & Rallo, G. (2018). On the use of the eddy covariance latent heat flux and sap flow transpiration for the validation of a surface energy balance model. *Remote Sensing*, 10(2), 195.
3. Awada, H., Ciraolo, G., Maltese, A., Hidalgo, M. M., Provenzano, G., & Còrcoles, J. I. (2017, November). Assessing actual evapotranspiration via surface energy balance aiming to optimize water and energy consumption in large scale pressurized irrigation systems. In *Remote Sensing for Agriculture, Ecosystems, and Hydrology XIX* (Vol. 10421, p. 104210G). International Society for Optics and Photonics.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, evapotranspiration, multi-platform sensing, poplar, UAV

Presentation type: oral

A multi-platform approach to dissect the evapotranspiration response to drought of black poplar

Flavia Tauro^{1*}, Antonino Maltese², Antoine Harfouche¹, Salvatore Grimaldi¹

¹ Department for Innovation in Biological, Agro-food and Forest systems, University of Tuscia, Via San Camillo de Lellis, 01100 Viterbo (VT), Italy (corresponding: flavia.tauro@unitus.it)

² Department of Engineering, University of Palermo, Palermo 90128, Italy

High-throughput mapping of evapotranspiration (ET) is paramount to optimize water resources management and to accelerate forest tree genetic improvement against drought environmental stress. Ideally, investigation of the energy response at the tree level may promote tailored irrigation strategies and, thus, increase biomass productivity. However, data availability is limited and planning experimental campaigns can be complex. To this end, a multi-platform observational approach was adopted herein to dissect ET signature of a full-sib F₂ partially inbred poplar population (“POP6”) at the canopy level. POP6 comprised more than 4600 trees representing 503 genotypes, whose F₁ was obtained from an intraspecific controlled cross between two *P. nigra* parents originated from natural populations in divergent environmental conditions [1]. Trees were located in two adjacent plots where different irrigation treatments (moderate drought and well-watered) were maintained.

Data collected from satellite and unmanned aerial vehicles remote sensing as well as ground-based sensors were integrated at consistent spatial aggregation and combined to compute the surface energy balance of the trees through a modified Priestley-Taylor approach.

ET response was significantly different between well irrigated and water limited trees, whereby genotypes in moderate drought conditions exhibited larger standard deviations. Genotypes classified as drought tolerant based on the stress susceptibility index (SSI) presented ET values significantly higher than the rest of the population. This study confirmed that water limitation in moderate drought field settings led to reduced soil moisture in the tree root zone and, therefore, to lower ET rates.

References

1. Ludovisi, R., Tauro, F., Salvati, R., Khoury, S., Scarascia Mugnozza, G., Harfouche, A., 2017. UAV-based thermal imaging for high-throughput field phenotyping of black poplar response to drought. *Frontiers in Plant Science*, 8, 1681. doi:10.3389/fpls.2017.01681.



Reference topic: remote sensing, NDVI, vineyard

Presentation type: oral

Comparison of remote and ground sensing technologies to compute NDVI values of diseased and healthy grapevine

Gabriele Daglio^{1*}, Damiano Zampieri², Raimondo Gallo², Fabrizio Mazzetto¹

¹ Faculty of Science and Technology, Free University of Bozen (FUB) Piazza Università 5, 39100 Bolzano (BZ), Italy (corresponding: gabriele.daglio@unibz.it)

In precision agriculture several tools can be used to obtain rigorous information about the health status of the plants, as showed by several authors as Kerckech et al. (2020) and Al-Saddik et al. (2017).

This work proposes the comparison of two different approaches able to compute the NDVI value of diseased and healthy plants in a vineyard. The tests were carried out on *Vitis vinifera* plants cv. Dolcetto and Barbera. The following instrumentation was used during the test: i) Unmanned aerial vehicle (UAV) multicopter equipped with a multispectral camera, ii) a tracked bin carrier vehicle (ByeLab) equipped with multiple devices.

The grapevines were categorized in healthy, low and high diseased and their position were georeferenced during a ground manual survey. Two UAV flew at different altitudes (30-70 meters) were made and the images collected by the multispectral camera were elaborated to compute the NDVI maps associating the NDVI value at each plant with QGIS. At the same time, the canopies of four vine rows were scanned two times with the ByeLab assessing the reflectance of every single plants. These data were analyzed using Matlab.

All NDVI values has been classified in the same categories as the ground survey.

For healthy plants we obtained values between 0.70 and 0.75 (Dolcetto cv), while for Barbera cv the values were between 0.70 to 0.73. Diseased plants showed lower NDVI values than the healthy plants for each cultivar at 0.64-0.70 (Dolcetto cv) and 0.68-0.7 (Barbera cv). This trend was detected for both the surveys, suggesting that both the technologies discern healthy from diseased plants.

References

1. M. Kerckech, A. Hafiane, and R. Canals, 2020, "Vine disease detection in UAV multispectral images using optimized image registration and deep learning segmentation approach," *Comput. Electron. Agric.*, vol. 174.
2. H. Al-Saddik, A. Laybros, B. Billiot, and F. Cointault, 2018, "Using image texture and spectral reflectance analysis to detect Yellowness and Esca in grapevines at leaf-level," *Remote Sens.*, vol. 10, no. 4.
3. G. Ristorto, R. Gallo, A. Gasparetto, L. Scalera, R. Vidoni, and F. Mazzetto, 2017, "Using image texture and spectral reflectance analysis to detect Yellowness and Esca in grapevines at leaf-level," *Remote Sens.*, vol. 10, no.4.



Panel 2 - Vegetation & Land Use

Reference topic: remote sensing, river management, satellite imagery

Presentation type: oral (**invited talk**)

Monitoring from close-range remote sensing the hydraulic resistance (Manning) of agricultural channel network

Jean-Stéphane Bailly^{1,2*}, Fabrice Vinatier¹, Gabrielle Rudi³

¹LISAH, Univ Montpellier, INRAE, IRD, Institut Agro, Montpellier, France (corresponding: bailly@agroparistech.fr)

²AgroParisTech, Paris, 75005, France

³G-Eau, Univ Montpellier, AgroParisTech, CIRAD, INRAE, IRD, Institut Agro, Montpellier, France

Ditch vegetation has numerous positive effects on the main regulating services of agricultural channels, such as seed retention, pollutant mitigation, bank stabilization, and sedimentation. The channel vegetation also limits the water conveyance, and consequently is frequently removed by farmers (management practices) to increase its porosity and consequently decrease the hydraulic resistance. A large body of literature attempts to characterize vegetation characteristics affecting hydraulic resistance, through the introduction of the blockage factor of flow by vegetation. However, this factor has multiple definitions and is still difficult to assess in the fields with actual and diverse vegetation covers, especially for grassy plants of channels. In addition, the temporal variability resulting from growing vegetation and management practices make the objective monitoring of hydraulic resistance in channels highly challenging. Close-range remote sensing (photogrammetry, Flash Lidars) offers possibilities now to get time series of complex channel vegetation characteristics but up to know, it has never been studied up to the hydraulic resistance monitoring. This talk is presenting two experiments trying to overpass this challenge.

In the first experiment, we present an approach using a photogrammetric technique (SfM-MVS) to construct time series of herbaceous vegetation porosity (3D point clouds) in a real agricultural channel (ditch) variously managed by farmers. After point clouds time-series analysis, an indicator of vegetation porosity for the whole section and of the surface of the channel is computed. Results show that mowing and chemical weeding are the practices presenting the most favorable temporal evolutions of the porosity indicators regarding flow events. Burning did not succeed in restoring the porosity of the channel due to quick recovery of the vegetation and dephasing of the maintenance calendar with the flow events.

In the second experiment, we aim at predicting flow resistance from 3D vegetation characteristics using a close-range laser scanner also providing 3D point clouds. Flow resistance and vegetation 3D characteristics were defined using Manning coefficient and blockage factors, respectively. We tested combined effects of flow discharge against plant species and densities characterizing intermittent channels in a controlled channel flume. Our results showed a variability of Manning coefficient describing flow rugosity against species and densities, with a highest rugosity for sclerophyllous species than herbaceous ones. Different blockage factors were calculated on the basis of scan clouds



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

linked to Manning coefficients using non linear equation. The best relationship ($R^2 = 0.9$) were found for non linear equation relating Manning coefficients to a simplified blockage factor figuring the mean vegetation height deduced from the projection of the scan point cloud to the channel frontal area.

Linking these two experiments offers new possibilities to objectively monitor the hydraulic resistance of agricultural channel networks from 3D remote sensing sensors.

References

1. Vinatier, F, Bailly, J-S, Belaud, G. From 3D grassy vegetation point cloud to hydraulic resistance: Application to close-range estimation of Manning coefficients for intermittent open channels. *Ecohydrology*. 2017; 10: e1885. <https://doi.org/10.1002/eco.1885>
2. Vinatier, F.; Dollinger, J.; Rudi, G.; Feurer, D.; Belaud, G.; Bailly, J.-S. The Use of Photogrammetry to Construct Time Series of Vegetation Permeability to Water and Seed Transport in Agricultural Waterways. *Remote Sens*. 2018, 10, 2050.



Reference topic: remote sensing, digital terrain analysis, soil hydrological properties

Presentation type: oral

Assessment of the riparian leaf density using different satellite imagery in a mountain stream

Giovanni Romano¹, Giovanni Francesco Ricci^{1*}, Francesco Gentile¹

¹ Department of Agricultural and Environmental Sciences, University of Bari Aldo Moro, Bari 70032, Italy
(corresponding: giovanni.ricci@uniba.it)

In the last years, remote sensing techniques may provide a useful tool in retrieving Vegetation indices (VIs) and evaluating vegetation features. Image pixel resolution can affect data analysis and results accuracy. The potential of three satellite images in retrieving the Leaf Area Index (LAI), with high and medium resolution (Pleiades 1A, Sentinel-2 and Landsat 8) was tested in two Mediterranean streams, in a nearby deciduous forest and in a winter wheat field.

The Caraux-Garson, the Lambert-Beer, and the Campbell-Norman equations were used to calculate LAI from the Normalized Difference Vegetation Index (NDVI). To validate the sensor data observed LAI values were detected in-situ with the Licor LAI 2200 Plant Canopy Analyzer and compared with LAI retrieved from the satellite imagery. Generally, Pleiades 1A and Landsat 8 images performed better statistical results than Sentinel-2. The former in deciduous forest or in sites characterized by stable riparian vegetation with high canopy closure, the latter in winter wheat sites or in stream reaches where the vegetation cover was homogenous or, conversely, almost absent. Sentinel-2 images provided more accurate results in terms of the range of LAI values. Regarding the different equation used, the Lambert-Beer generally performed best in estimating LAI, especially in areas, such as deciduous forests, that are geomorphologically stable or with a denser vegetation cover.

References

1. Romano, G.; Ricci, G.F.; Gentile, F. (2020), Influence of Different Satellite Imagery on the Analysis of Riparian Leaf Density in a Mountain Stream. *Remote Sensing*. 2020, 12, 3376; doi:10.3390/rs12203376
2. Romano, G.; Ricci, G.F.; Gentile, F. (2020). Comparing LAI Field Measurements and Remote Sensing to Assess the Influence of Check Dams on Riparian Vegetation Cover. In *Lecture Notes in Civil Engineering*; Coppola, A., Di Renzo, G., Altieri, G., D'Antonio, P., Eds.; Springer: Berlin, Germany, 2020; Volume 67, pp. 109–116.
3. Ricci G.F, Romano G., Leronna V., Gentile F. (2019). Effect of check dams on riparian vegetation cover: A multiscale approach based on field measurements and satellite images for Leaf Area Index assessment. *Science of the Total Environment*, 657, 827-838.
4. Abdelwahab O.M.M., Ricci G.F., De Girolamo A.M., Gentile, F. (2018). Modelling soil erosion in a Mediterranean watershed: Comparison between SWAT and AnnAGNPS models. *Environmental Research*, 166, 363-376.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, vineyards, grass

Presentation type: oral

Use of remotely sensed data for the evaluation of inter-row cover intensity in vineyards

Francesco Palazzi¹, Marcella Biddoccu^{1*}, Enrico Borgogno Mondino², Eugenio Cavallo¹

¹*Istituto di Scienze e Tecnologie per l'Energia e Mobilità Sostenibili (STEMS) – Consiglio Nazionale delle Ricerche (CNR), Sede Secondaria di Torino (corresponding: marcella.biddoccu@cnr.it)*

²*Dipartimento di Scienze Agrarie, Forestali e Alimentari (DISAFA) – Università degli Studi di Torino, Grugliasco (TO).*

Vineyards are a high-income crop and can also have an important landscape value, especially in certain areas of Italy. Vineyards show large soil erosion rates depending on climate variability, local topography and vine management. Farming machineries can also determine compaction and affect soil hydraulic properties, runoff and erosion at different levels depending on inter-rows soil management.

This work, with focus on a pilot area located in the municipality of Carpeneto, Alessandria province (Piedmont, NW Italy), concerns the adoption of satellite optical data from the Copernicus Sentinel 2 (S2) mission to describe vineyard properties. A first analysis was addressed at testing if and how S2 data can map differences in vineyards management and behaviour. It was achieved at field level with reference to some experimental plots presenting different inter-row soil management (tillage -CT-, tillage with downstream 10-m-strip grass cover -ST- and total permanent grass cover -GC-). Reference vineyards were placed on sloping areas and set with up-and-down tillage ('rittochino' in Italian language). A NDVI image time series (TS) was obtained from the level 2 S2 data for the growing season 2017-2018. TS was processed at plot level and proved to be effective in showing vegetation response to mechanical interventions during the growing season; in particular ripping in CT and shredding in GC in late spring and, during summer, mowing and topping were highlighted; minor variations in NDVI were observed after harvest in all plots.

Secondly, a wider analysis was achieved including all the vineyards located in the municipality of Carpeneto. These were mapped by photo-interpretation and grouped in clusters with reference to the local NDVI TS (averaged at plot level). Clustering was obtained by K-means unsupervised classification. Results suggest that vineyards can be classified according to the intensity of inter-row's soil management.

A further analysis was aimed at exploring the role of the native S2 bands in describing vineyard differences and inter-row coverage. Preliminary results suggest that single-bands data could be jointly used with vegetation indices to better describe vine growth dynamics in row-crops. Further studies on remotely sensed data could provide spatially variable inputs for applications in erosion risk management and land analysis.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, Unmanned Aerial Vehicle (UAV), Light Detection And Ranging (LiDAR), tree metrics, forestry

Presentation type: oral

Comparison between two methodologies for the Individual Tree Height Estimation through a LiDAR mounted on a drone

Monica F. Rinaldi^{1*}, Gabriele Daglio¹, Raimondo Gallo¹, and Fabrizio Mazzetto¹

¹ Faculty of Science and Technology, Free University of Bozen–Bolzano, Piazza Università 5, I-39100 Bolzano, Italy
(corresponding: MonicaFernanda.Rinaldi@unibz.it – ID-ORCID: 0000-0002-8939-7766)

Nowadays, forest areas can be assess using Unmanned Aerial Vehicle (UAV) carrying a Light Detection And Ranging (LiDAR) sensor in order to estimate the tree metrics. A forest area in Alto-Adige Region – Italy was selected for this study where an aerial survey was conducted with the Yellowscan Surveyor device mounted on a DJI S900. The aim of this research was to identify the individual tree crown (ITC) in order to estimate the tree height (TH) through a Point Cloud Segmentation and Canopy Height Model (CHM) Segmentation. The results were also compared with ground based measurements monitoring where the location of each tree was georeferenced, and the TH was measured through a Haglöf vertex. The expected result is to obtain the most accurate TH estimator for the study area to propose a reliable solution for a fast and precise above ground biomass volume estimation in forestry inventories.

The data for this research was collected during the WEQUAL Project “Web service centre for a QUALity multidimensional design and tele-operated monitoring of Green Infrastructures” developed withing the European EFRE-FESR Südtirol-Alto Adige framework.

References

1. Rinaldi, Monica F, Gallo, Raimondo, Daglio, Gabriele, and Mazzetto, Fabrizio. "An Innovative Methodology to Be More Time-Efficient When Analyzing Data in Precision Viticulture." *Innovative Biosystems Engineering for Sustainable Agriculture, Forestry and Food Production*. Vol. 67. Cham: Springer International, 2020. 783-92. *Lecture Notes in Civil Engineering*.
2. Gallo, Raimondo, Ristorto, Gianluca, Bojeri, Alex, Zorzi, Nadia, Daglio, Gabriele, Rinaldi, Monica Fernanda, Sauli, Giuliano, and Mazzetto, Fabrizio. "Assessment of Riparian Environments through Semi-automated Procedures for the Computation of Eco-morphological Indicators: Preliminary Results of the WEQUAL Project." *Die Bodenkultur: Journal of Land Management, Food and Environment* 70.3 (2019): 131-45.
3. Rinaldi, Mónica Fernanda, Llorens Calveras, Jordi, and Gil Moya, Emilio. "Electronic Characterization of the Phenological Stages of Grapevine Using a LIDAR Sensor." (2013).



Reference topic: remote sensing, burned area detection,
Presentation type: oral

Sentinel-1 SAR satellite data and open-source Python algorithms for unsupervised burned area detection in Mediterranean ecosystems

Giandomenico De Luca¹, João M.N. Silva², Giuseppe Modica^{1*}

¹ *Dipartimento di Agraria, Università degli Studi Mediterranea di Reggio Calabria, Località Feo di Vito, I-89122 Reggio Calabria, Italy (corresponding: giuseppe.modica@unirc.it)*

² *Forest Research Centre, Instituto Superior de Agronomia, University of Lisbon, Tapada da Ajuda, 1349-017 Lisbon, Portugal.*

In this research, we explore the capability of the free synthetic aperture radar (SAR) Sentinel-1 (S-1) C-band data to map burned areas in the Mediterranean forest ecosystems. The workflow is based on unsupervised machine learning open-source processing developed in python-based scripts, the ESA SNAP-Python interface (ESA snappy) for S-1 image pre-processing, and the Scikit-learn libraries for the image processing and classification.

We used a multitemporal filter to reduce the speckle noise effects and the backscatter time-averages of pre- and post-fire datasets. The contrast between changed and unchanged areas was enforced by calculating two mono-polarimetric radar indices, the radar burn difference (RBD) and logarithmic radar burn ratio (LogRBR), and two temporal difference of dual-polarimetric radar indices (delta modified radar vegetation index (ΔRVI), delta dual-polarization SAR vegetation index $\Delta DPSVI$), exhibiting greater sensitivity to the backscatter changes. We enhanced the spatial details and the scene's contrast by extracting the Gray Level Co-occurrence Matrix (GLCM) textures (dissimilarity, entropy, correlation, mean, and variance) from the four indices and using them as input image layers. The burned area was delineated through unsupervised classification using the k-means machine learning algorithm, and the number of clusters was set using a silhouette score analysis. To assess the accuracy of the resulting detected burned areas, the recall (r), precision (p), and the F-score accuracy metrics were calculated. The obtained results confirm the satisfactory performances of the proposed approach. Moreover, the proposed workflow, wholly based on free and open-source software and data, offers high adaptation flexibility, repeatability, and custom improvement.

References

1. Modica, G., Messina, G., De Luca, G., Fiozzo, V., & Praticò, S. (2020). Monitoring the vegetation vigor in heterogeneous citrus and olive orchards. A multiscale object-based approach to extract trees' crowns from UAV multispectral imagery. *Computers and Electronics in Agriculture*, 175, 105500. <https://doi.org/10.1016/j.compag.2020.105500>
2. De Luca, G., N. Silva, J. M., Cerasoli, S., Araújo, J., Campos, J., Di Fazio, S., & Modica, G. (2019). Object-Based Land Cover Classification of Cork Oak Woodlands using UAV Imagery and Orfeo ToolBox. *Remote Sensing*, 11(10), 1238. <https://doi.org/10.3390/rs11101238>
3. De Luca, G., Modica, G., Fattore, C., & Lasaponara, R. (2020). Unsupervised Burned Area Mapping in a Protected Natural Site. An Approach Using SAR Sentinel-1 Data and K-mean Algorithm. In Gervasi O. et al. (eds) (Ed.), *Computational Science and Its Applications – ICCSA 2020. Lecture Notes in Computer Science, vol 12253* (pp. 63–77). Springer Nature. https://doi.org/10.1007/978-3-030-58814-4_5



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topics: remote sensing, LULC, Sentinel-2, Google Earth Engine, Machine learning, GEOBIA
Presentation type: oral

LULC object-oriented classification in Google Earth Engine: an application in the Trasimeno Lake area

Andrea Tassi¹, Marco Vizzari^{1*}

¹ *Department of Agricultural, Food and Environmental Sciences, University of Perugia, Borgo XX Giugno 74, 06124, Perugia, Italy (corresponding: marco.vizzari@unipg.it)*

LULC (Land-Use/Land-Cover) maps play a key role in landscape monitoring and assessment, supporting the definition of policies and strategies for sustainable landscape planning and management. Google Earth Engine (GEE) is a free, cloud-based geospatial analysis platform that allows users to solve in a very efficient way the primary problems related to the storage of huge amounts of remote sensing data, their management, processing, and analysis. Machine Learning algorithms (e.g. Random Forest – RF) combined with object-oriented techniques (GEOBIA – Geographic Object-Based Image Analysis) for LULC classification is still no common in this environment. In this direction, this work is aimed at implementing a GEOBIA approach, combined with an RF algorithm, in a user-friendly GEE code which allows the user to produce a LULC classification and assess its accuracy through a confusion matrix and a kappa statistic. The proposed procedure was tested in a study area, 154.4 Km² wide, located in the Lake Trasimeno area (central Italy), using Sentinel 2 data. The area was selected considering its complex LULC mosaic mainly composed of artificial surfaces, annual and permanent crops, small lakes, and wooded areas. In this study area, the approach produced a very good overall accuracy and the kappa statistics (86% and 0.82). The code application has shown high reliability of the whole process, even though the object-oriented classification results quite computational demanding and tends to slow down the code execution.

References

1. Benincasa, P.; Antognelli, S.; Brunetti, L.; Fabbri, C.A.; Natale, A.; Sartoretti, V.; Modeo, G.; Guiducci, M.; Tei, F.; Vizzari, M. Reliability of NDVI derived by high resolution satellite and UAV compared to in-field methods for the evaluation of early crop N status and grain yield in wheat. *Exp. Agric.* 2017, 1–19, doi:10.1017/S0014479717000278.
2. Messina, G.; Peña, J.M.; Vizzari, M.; Modica, G. A Comparison of UAV and Satellites Multispectral Imagery in Monitoring Onion Crop. An Application in the ‘Cipolla Rossa di Tropea’ (Italy). *Remote Sens.* 2020, 12, 3424, doi:10.3390/rs12203424.
3. Tassi, A.; Gil, A. A Low-cost Sentinel-2 Data and Rao’s Q Diversity Index-based Application for Detecting, Assessing and Monitoring Coastal Land-cover/Land-use Changes at High Spatial Resolution. *J. Coast. Res.* 2020, doi:10.2112/SI95-253.1.
4. Vizzari, M.; Santaga, F.; Benincasa, P. Sentinel 2-based nitrogen VRT fertilization in wheat: Comparison between traditional and simple precision practices. *Agronomy* 2019, 9, doi:10.3390/agronomy9060278.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, green infrastructure, sustainable management of urban green network

Presentation type: oral

Designing and implementing a multifunctional network of urban green infrastructures

Stefano Chiappini^{1*}, Francesco Paci¹, Nicole Hofmann¹, Andrea Galli¹, Adriano Mancini³ and Ernesto Marcheggiani^{1,2}

¹ *Department of Agriculture, Food and Environmental Sciences, Università Politecnica delle Marche, Ancona, Via Brezze Bianche 10, 60131, Ancona (AN), Italy*

² *Division of Forest, Nature and Landscape (FNL), University of Leuven, Celestijnenlaan 200e, 3001 Leuven (Belgium) (corresponding: stefano.chiappini@staff.univpm.it)*

³ *Department of Information Engineering, Università Politecnica delle Marche, Ancona, Via Brezze Bianche 10, 60131, Ancona (AN), Italy*

With the occasion of the meeting in Padova, we would like to present a work about the possibilities offered by nowadays jointed advanced and traditional geomatics approaches. The experiment sets a multi-disciplinary environment, where botanists, planners, agronomists, software and geospatial engineers teaming up to offer the city of Ancona a bold solution to manage urban green infrastructures and the rich cultural heritage attached to them.

Along with a previous initiative, the Cost Action Cyberparks aiming at shedding light on the potentials of communication technologies and ICTs to foster the multifunctional role of green urban areas, the ongoing project "The network of botanical gardens" follows the same path. Aiming at far-reaching meaningful results and thanks to the promising outcomes gotten previously for the city park Cardeto as published in (1 and 2), we expanded the study area to three new parks and botanical gardens: Selva di Gallignano, the garden of Montedago and the marine Falesia, which altogether make up the backbone of the whole city green fabric.

Several devices, such as 3D and thermal Cameras or Beacons, and a set of surveys (Global Navigation Satellite Systems and UAVs) have been performed to dress the area with sets of cyber sensors creating a flux of information about positional and phenological characteristics of the city green infrastructures along the course of time. This flux of information, if soundly streamed to the city public shall make the object of a future experiment to prove that gamification and socialisation of urban green values could represent a cornerstone to urban green monitoring, planning and design.

References

1. Roberto Pierdicca, Marina Paolanti, Raffaele Vaira, Ernesto Marcheggiani, Eva Savina Malinverni, Emanuele Frontoni (2019) Identifying the use of a park based on clusters of visitors' movements from mobile phone data, *Journal of Spatial Information Science, JOSIS*, No 19 (2019), pp 29-52
2. Khromova, A., Smaniotto Costa, C., Erjavec, I. Š., Pierdicca, R., Malinverni, E. S., Galli, A., & Marcheggiani, E. (2016). Is the mediated public open space a smart place? Relationships between urban landscapes and ICT. The Cost Action TU 1306 CyberParks. *SCIRES-IT-SCientific RESearch and Information Technology*, 6(2), 17-28. <http://dx.doi.org/10.2423/i22394303v6n2p17>



Panel 3 – Digital Terrain Analysis & Soil Erosion

Reference topic: remote sensing

Presentation type: oral (invited talk)

Topography meter: remote sensing with a novel 3D surface measuring technique

Xiangzhou Xu

School of Hydraulic Engineering, Dalian University of Technology, Dalian 116024, China (corresponding: xzxu@dlut.edu.cn)

Gravity erosion is one of the most remarkable natural hazards in mountainous regions, especially on the Loess Plateau of China. Nevertheless, the measurement of failure mass is very difficult because gravity erosion usually occurs randomly and it combines with hydraulic erosion. Here we present a novel testing technique that could quantitatively measure time-variable gravity erosion on the steep loess slopes. A structured light 3D surface measuring apparatus, the Topography Meter, was designed and manufactured in our laboratory. Dynamic variation of the steep slope relief was monitored under rainfall simulation and the slope deforming process was recorded by a computer video technology. With the help of laser marking, plane figures were transformed into 3D graphs, thus the shape of target surface was accurately computed. By comparing the slope geometries in the moments before and after the erosion incident on the snapshot images at a particular time, we could obtain the volume of gravity erosion and many other erosion data, including the volume of slide mass, the amount of soil loss eroded by overland flow, etc. A series of calibration tests were conducted and the results showed that the accuracy of this technique was high and sufficient for exploring the mechanism of slope erosion. More than 200 rainfall simulation events were subsequently tested with the apparatus, further confirming its feasibility and reliability.

References

1. Xu X, Zhu T, Zhang H, Gao L. 2020, Experimental Erosion: Theory and Practice of Soil Conservation Experiments, *Science Press and Springer Nature*, p1-247. (ISBN for Springer Nature: 978-981-15-3800-1; ISBN for Science Press: 978-7-03-064566-1; in English)
2. Xu X, Ma Y, Yang W, Zhang H, Tarolli P, Jiang Y, Yan Q. 2020, Qualifying mass failures on loess gully sidewalls using laboratory experimentation. *Catena*, 187: 104252 (12).
3. Xu X-Z*, Zhang H-W, Wang W-L, Zhao C, Yan Q. 2015, Quantitative monitoring of gravity erosion using a novel 3D surface measuring technique: validation and case study. *Natural Hazards*, 75(2): 1927–1939.



Reference topic: remote sensing, data fusion; TLS; SfM; agricultural terrace; coregistration; direct georeferencing

AIIA section: 7 section

Presentation type: oral

Monitoring of vegetated agricultural terraces systems through SfM-TLS data fusion technique

Sara Cucchiaro^{1,2*}, Daniel J. Fallu³, Antony G. Brown³, Paolo Trolli²

¹ *Department of Agricultural, Food, Environmental and Animal Sciences, University of Udine, Via delle Scienze, 206, 33100 Udine, Italy (corresponding: sara.cucchiaro@uniud.it)*

² *Department of Land, Environment, Agriculture and Forestry, University of Padova, Agripolis, Viale dell'Università 16, 35020 Legnaro (PD), Italy*

³ *Tromsø University Museum, UiT The Arctic University of Norway, Kvaløyen 30, 9013 Tromsø, Norway*

Terraced landscapes can be considered a historical heritage and a cultural ecosystem service to be adequately preserved by increased soil degradation due to climate change and land abandonment. In the last two decades, important developments in High-Resolution Topographic (HRT) techniques, methods, sensors, and platforms has greatly improved our ability and opportunities in the assessment and monitoring of such cultural ecosystem services. However, due to the limitations imposed by rugged topography and the occurrence of vegetation, the application of a single HRT technique is challenging in these particular agricultural environments. Therefore, data fusion from different acquisition platforms can be a useful solution to overcome specific detection problems. Terrestrial laser scanning (TLS) and structure from motion (SfM) was tested for the first time in agricultural terraces context, to realize detailed digital terrain models (DTMs) of two sites, Soave (North-east of Italy) and Martelberg in Saint-Martens-Voeren (East Belgium), both characterized by the presence of vegetation that covers parts of the subvertical surfaces, complex morphology, and inaccessible areas. In the unreachable zones, where was impossible to locate the GCPs, we tested the direct georeferencing (DG) method, exploiting onboard multi-frequency GNSS receivers for unmanned aerial vehicles (UAVs) and post-processing kinematic (PPK) data. The research demonstrated how survey planning and co-registration were fundamental phases for data fusion that is required to obtain accurate DTMs that reflect the real surface roughness of terrace systems without gaps in data.

References

1. Cucchiaro, S., Fallu, D.J., Zhang, H., Walsh, K., Van Oost, K., Brown, A.G., Tarolli, P. Multiplatform-SfM and TLS Data Fusion for Monitoring Agricultural Terraces in Complex Topographic and Landcover Conditions. *Remote Sensing* 2020, 12, 1946.
2. Cucchiaro, S., Fallu, D.J., Zhao, P., Waddington, C., Cockcroft, D., Tarolli, P., Brown, A.G. SfM photogrammetry for GeoArchaeology. *Dev. Earth Surf. Process.* 2020, 23, 183–205.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, high resolution topography, soil erosion

Presentation type: oral (invited talk)

Soil erosion measurement across spatio-temporal scales

Anette Eltner¹

¹*Department of Environmental Sciences, Institute of Photogrammetry and Remote Sensing, Technische Universität Dresden, Helmholtzstr. 10, 01069 Dresden, Germany (corresponding: anette.eltner@tu-dresden.de)*

Soil erosion due to water is a worldwide phenomenon caused or increased by human cultivation. The quantification of the eroded soil material is a methodological challenge. Accurate estimation of soil erosion forms the basis for monitoring programs as well as modelling approaches. Modern methods for the generation of high-resolution 3D point clouds enable microscale recording of the soil surface and thus highly precise capturing of different erosion forms. In this talk, methods applicable on different scales for the recording of the consequences of different erosion processes and the subsequent quantification of soil loss are presented. The challenges and benefits of high-resolution and mm-accurate measurement of the soil surface will be demonstrated. Different (semi-)automated methods for determining erosion volumes based on 3D point data will be discussed. The introduced approaches enable event-based soil erosion assessment from plot to field scale.



Reference topic: remote sensing, Debris flow, Check dam, High-resolution topography, DTM, Multi-temporal analysis, Sediment connectivity

Presentation type: oral

Assessing sediment dynamics and torrent control works efficiency in a debris-flow catchment using multi-temporal topographic surveys

Federico Cazorzi¹, Sara Cucchiario^{1*}, Lorenzo Marchi², Marco Cavalli²

¹ *Department of Agricultural, Food, Environmental and Animal Sciences, University of Udine, Via delle Scienze, 206, 33100 Udine, Italy (corresponding: sara.cucchiario@uniud.it)*

² *CNR-IRPI, Italy*

Torrent control works have always been a fundamental tool for preventing torrential hazard in mountain catchments, where the sediment transport phenomena as debris flows are one of the most dangerous geomorphic processes affecting small steep basins. Among the hydraulic engineering structures, check dams represent one of the most common hydraulic engineering solutions to manage debris-flow risk. These structures could have important effects on sediment dynamics. In spite of the widespread presence of such hydraulic structures in steep mountain streams worldwide, very little researches considered the role of check dams on sediment dynamics in debris-flow environments over time to enhance the planning of the torrent control works. In the last two decades, High-Resolution Topography (HRT) has provided new opportunities to characterize debris-flow activity at different scales. In this research, the effects of check dams on debris-flow dynamics were investigated by means of multi-temporal SfM and LiDAR surveys in the Moscardo torrent (eastern Italian Alps) where several check dams have been built over time. Methodological workflows enabled the realization of multi-temporal Digital Terrain Models (DTMs) which were compared (i.e., DoD) to quantify the debris mobilized and the time evolution of erosion and deposition patterns in debris-flow channels equipped with check dams. The DoDs data were integrated with a sediment connectivity analysis to have a whole assessment of debris-flow dynamic. The results show that the check dams considerably modified debris-flow dynamics in the studied channel but their performance cannot be considered satisfactory. The analysis proposed could help to improve design approaches and, in this way, select better solutions.

References

1. Cucchiario, S., Cavalli, M., Vericat, D., Crema, S., Llana, M., Beinat, A., Marchi, L., Cazorzi, F. 2019a. Geomorphic Effectiveness of Check Dams in a Debris-flow Catchment Using Multitemporal Topographic Surveys. *Catena* 174: 73–83.
2. Cucchiario, S., Cazorzi, F., Marchi, L., Crema, S., Beinat, A., Cavalli, M. 2019b. Multi-temporal Analysis of the Role of Check Dams in a Debris-flow Channel: Linking Structural and Functional Connectivity. *Geomorphology* 345: 106844.
3. Cucchiario, S., Cavalli, M., Vericat, D., Crema, S., Llana, M., Beinat, A., Marchi, L. and Cazorzi, F. 2018. Monitoring topographic changes through 4D-structure-from-motion photogrammetry: application to a debris-flow channel. *Environ Earth Sci*, 2018, 77: 632.



Reference topic: remote sensing, digital terrain analysis, sediment transport

Presentation type: oral

Primary impacts and cascading processes of the Vaia storm in the Rio Cordon mountain catchment (Belluno Province)

Lorenzo Martini^{1*}, Giacomo Pellegrini¹, Riccardo Rainato¹, Lorenzo Picco^{1,2,3}

¹ *Department of Land, Environment, Agriculture and Forestry, University of Padova, Agripolis, Viale dell'Università 16, 35020 Legnaro (PD), Italy (corresponding: lorenzo.martini.2@phd.unipd.it)*

² *Universidad Austral de Chile, Faculty of Engineering, Valdivia, Chile*

³ *Universidad Austral de Chile, RINA – Natural and Anthropogenic Risks Research Center, Valdivia, Chile*

Mountain basins can be rapidly affected by large infrequent disturbances (LIDs), supplying high amounts of water, sediments, and large wood. Subsequent cascading processes are often underestimated although their understanding would improve the catchment management strategies. The recent improvements in the field of remote sensing have become essential for the analysis and monitoring of such chain of secondary events triggered by the LIDs. Therefore, this contribution aims at presenting the recent dynamics caused by the Vaia storm on the Rio Cordon basin (5 km², Veneto Region). The primary impact was investigated using LiDAR data (DoD technique), while the subsequent cascading processes were monitored with multiple UAV surveys at catchment and reach scale, respectively. Fourteen sediment source areas were activated along the hillslopes, contributing with a total amount of 450 m³. The main channel network was eroded, delivering 6,900 m³ to the outlet (Martini et al., 2020). Moreover, the Vaia storm was able to blow down 139 trees for a total amount of 106 m³ (Picco et al., 2020) that were removed afterwards. All these primary impacts are affecting the stability of the active channel and the surrounding areas. To better understand the ongoing and future dynamics, a detailed monitoring of the sediment suspended load has started. Continuous UAV surveys and water quality sonde are being used to assess the sediment transport. The combination of the remote sensing and field measurements represents a suitable and promising approach for an holistic view of the future developments in a mountain basin after a LID.

References

1. Mitas, L., Mitasova, H., 1998. Distributed soil erosion simulation for effective erosion prevention. *Water Resources Research*, 34, 505–516.
2. Martini L., Picco L., Rainato R., Pellegrini G., Lenzi M.A., Cavalli M., 2020. Investigating the geomorphic change in the Rio Cordon basin (Italy) after Vaia Storm. Proceedings of the 10th Conference on Fluvial Hydraulics (Delft, Netherlands, 7-10 July 2020). Taylor and Francis, ISBN 0367627736, 1774-1779. (<https://doi.org/10.1201/b22619>).
3. Picco L., Rainato R., Pellegrini G., Martini L., Lenzi M.A., Mao L., 2020. An extraordinary event changed the (morphological) appearance of a famous Alpine stream. Proceedings of the 10th Conference on Fluvial Hydraulics (Delft, Netherlands, 7-10 July 2020). Taylor and Francis, ISBN 0367627736, pp. 1653-1658. (<https://doi.org/10.1201/b22619>)



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: landslides; roads; agricultural systems; UAV; GIS

Presentation type: oral

UAV-SfM 4D mapping of landslides activated in steep terraced agricultural context

Luca Mauri^{1*}, Eugenio Straffellini¹, Sara Cucchiario^{2,1}, Paolo Tarolli¹

¹ *Department of Land, Environment, Agriculture and Forestry, University of Padova, Agripolis, Viale dell'Università 16, 35020 Legnaro (PD), Italy (corresponding: luca.mauri.2@phd.unipd.it)*

² *Department of Agricultural, Food, Environmental and Animal Sciences, University of Udine, Via delle Scienze, 206, 33100 Udine (UD), Italy*

The presence of roads is closely linked with the activation of land degradative phenomena such as landslides (Sidle and Ziegler, 2012). In agricultural contexts, road networks bring numerous advantages in economic and logistic terms, representing a crucial infrastructure for farm management and production. However, factors such as ineffective road management and design, as well as specific geomorphological elements like terrain slope, soil characteristics and local rainfall regimes actively influence landslides occurrence. In this context, high-resolution topography data can provide useful information to more in-depth investigate the presented issue. Indeed, recent developments in digital photogrammetry (e.g. Structure from Motion; SfM) paired with UAV systems increase our possibilities to realize low-cost and recurrent topographic surveys (Siebert and Teizer, 2014). This allows the realization of multi-temporal (hereafter 4D) and high-resolution Digital Elevation Models (DEMs), fundamental to analyse geomorphological features and quantify processes at the fine spatial and temporal resolutions at which they occur. This research aims to propose a multi-temporal comparison of the main geomorphometric indicators describing a landslide-prone terraced vineyard, in order to assess the observed high-steep slope failures. The possibility to investigate the evolution of landslides affecting steep agricultural systems through high-resolution and 4D comparison of such indicators is still a challenge to be investigated. In this article we considered a case study located in the central Italian Alps, where two landslides were activated below a rural road within a terraced agricultural system. Multi-temporal computation of Relative Path Impact Index, terrain curvature, roughness and features extraction were derived from SfM-based DEMs reconstruction. The dynamics of the landslides were monitored through the comparison of repeated DEMs (DEM of Difference, i.e. DoD), that offers essential information on the evolution of erosion and deposition patterns, and allows the volumes quantification of topographic changes. The results highlight the usefulness of high-resolution and 4D UAV-based SfM surveys for the investigation of landslides triggering due to the presence of roads at hillslope scale in agricultural systems. This work could be a useful starting point for further investigations of landslide-susceptible zones at wider scale, in order to preserve the quality and the productivity of affected agricultural areas. In addition, the alteration of superficial water and sediment flows, due to the presence of the road close to landslide zones, could be implemented through the adoption of specific hydrological models, such as SIMWE (Mitasova et al., 2103).



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

References

1. Sidle RC, Ziegler AD. 2012. The dilemma of mountain roads. *Nature Geosciences* 5: 437–438. DOI: 10.1038/ngeo1512
2. Siebert S, Teizer J. 2014. Mobile 3D mapping for surveying earthwork projects using an Unmanned Aerial Vehicle (UAV) system. *Automation in construction* 41: 1–14.
3. Mitasova H, Barton M, Ullah I, Hofierka J, Harmon R. 2013. GIS-Based Soil Erosion Modeling. In *Treatise on Geomorphology* (Vol. 3, pp. 228–258). Elsevier Inc.



Panel 4 – Water Resources Management

Reference topic: remote sensing, digital terrain analysis, gully erosion, landslides

Presentation type: oral (invited talk)

Abandoned reservoirs and gully erosion analysis using LiDAR

Mihai Niculita¹

¹ Department of Geography, Faculty of Geography and Geology, Alexandru Ioan Cuza University of Iasi, Carol I 20A, 700505 Iasi (IS), Romania (corresponding: mihai.niculita@uaic.ro)

Gullies and landslides are processes that have an important role in erosion, and for soil erosion especially from an anthropic point of view. Although spatially these processes do not have an important extension for agricultural lands, from a rate of change perspective, are important, because the dynamics of these processes impose tough restrictions for agriculture. The availability for wide areas of high-resolution LiDAR DEMs and the availability of affordable SfM technology (camera, drone/UAV, software) with which high-resolution DEMs can be obtained, opens the possibility of rate of change monitoring. By applying rate of change techniques (DoD/Geomorphic Change Detection), precise monitoring of gullies and landslides can be achieved, which coupled with geomorphological mapping on the high-resolution imagery and DEM can greatly improve the understanding of the evolution of these processes, in order to be able to apply remedial measures. A study case of gullies developed on abandoned reservoir bottoms is presented with two methodological perspectives: geomorphometric detection and geomorphic change detection.

References

1. Niculiță M (2016) Automatic landslide length and width estimation based on the geometric processing of the bounding box and the geomorphometric analysis of DEMs. *Natural Hazards and Earth System Science*, 16, 2021-2030.
2. Niculiță M, Mărgărint MC, Tarolli P (2020) Using UAV and LIDAR data for gully geomorphic changes monitoring, in: Tarolli P, Mudd S, (eds.), Remote Sensing of Geomorphology. *Developments in Earth Surface Processes*, vol. 23, Elsevier, pp. 271-315.
3. Niculiță M, Balan M-G, Andrei A, Rusu E (2019) Digital soil mapping in a mountainous area with mixed land use (Humor catchment – Eastern Carpathians, Romania) using soil-landscape systems, fuzzy logic and environmental covariates. *Environmental Engineering and Management Journal*, 18(2), 479-479.
4. Niculiță M (2020) Geomorphometric Methods for Burial Mound Recognition and Extraction from High-Resolution LiDAR DEMs. *Sensors*, 20(4), 1192.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, hydrology, soil moisture, watershed protection, terracing, water harvesting
Presentation type: oral

Remote Sensing advances in agricultural hydraulics and watershed protection

Giulio Castelli^{1,2,3*}, Elena Bresci^{1,2,3}, Daniele Penna^{1,4}, Federico Preti^{1,4}

¹ *Dipartimento di Scienze e Tecnologie Agrarie, Alimentari, Ambientali e Forestali (DAGRI), Università degli Studi di Firenze, Firenze, Italy (corresponding: giulio.castelli@unifi.it)*

² *Water Harvesting Lab, DAGRI*

³ *COPERNICUS Research Unit, Università degli Studi di Firenze*

⁴ *Laboratory of Environmental-Hydrological Modelling and Soil and Water Bioengineering (MAIN), DAGRI*

Among the different sectors of agricultural engineering, remote sensing has represented a ground-breaking innovation in the field of agricultural hydraulics and watershed protection due to the availability of new sensors and supports (Unmanned Aerial Vehicles – UAVs)¹ and advanced platforms for data analysis (Google Earth Engine)². The combination of such technologies opened new possibilities for monitoring hydrological processes, from snow cover³ to soil moisture⁴, and the effect of soil and water conservation structures⁴, with multi-scale options (from the single structure to the agricultural/hilly catchment area), across different geographic areas and climates. The present contribution will examine a portfolio of possible innovative applications of remote sensing in the field of agricultural hydraulics and watershed protection, built on the experiences of the group at the Università degli Studi di Firenze, analyzing possible development pathways, synergies with other sectors, and future technological advancements (e.g. High-altitude platform station (HAPS) or FAO EarthMap - <https://earthmap.org/>).

References

1. Tucci, G., Parisi, E. I., Castelli, G., Errico, A., Corongiu, M., Sona, G., Viviani, E., Bresci, E., Preti, F., 2019. Multi-Sensor UAV Application for Thermal Analysis on a Dry-Stone Terraced Vineyard in Rural Tuscany Landscape. *ISPRS International Journal of Geo-Information*, 8(2), 87. <http://doi.org/10.3390/IJGI8020087>
2. Castelli, G., Castelli, F., Bresci, E. 2019. Mesoclimate regulation induced by landscape restoration and water harvesting in agroecosystems of the horn of Africa. *Agriculture, Ecosystems & Environment*, 275, 54–64. <https://doi.org/10.1016/j.agee.2019.02.002>
3. Guastini, E., Zuecco, G., Errico, A., Castelli, G., Bresci, E., Preti, F., Penna, D. 2019. How does streamflow response vary with spatial scale? Analysis of controls in three nested Alpine catchments. *Journal of Hydrology*, 570, 705–718. <https://doi.org/10.1016/j.jhydrol.2019.01.022>
4. Castelli, G., Oliveira, L. A. A., Abdelli, F., Dhaou, H., Bresci, E., Ouessar, M. 2019. Effect of traditional check dams (jessour) on soil and olive trees water status in Tunisia. *Science of The Total Environment*. <https://doi.org/10.1016/j.scitotenv.2019.06.514>



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, river management, satellite imagery

Presentation type: oral

Analysis of time-series satellite images as a tool for planning river management strategies

Paolo Fogliata^{1*}, Daniele Masseroni¹, Alessio Cislighi^{1,2}, Gian Battista Bischetti^{1,2}

¹*Department of Agricultural and Environmental Sciences-Production, Landscape and Agroenergy, University of Milan, Via Celoria 2, Milan 20133, Italy (corresponding: paolo.fogliata@unimi.it)*

²*Centre of Applied Studies for the Sustainable Management and Protection of Mountain Areas-Ge.S.Di.Mont., University of Milan, Via Morino 8, Edolo 25048, Brescia, Italy*

River management requires actions based on best practices aim to combine hydraulic safety, river functionality, and ecological/environmental quality. Planning such actions require a detailed awareness of past river processes and a reliable prediction of their consequences on the fluvial inheritance (Scorpio, 2020). In this context, remote sensing technologies, applied for identifying the river changes, offer a viable decision-making instrument (Piégay, 2020). In particular, time-series satellite images are valid data to detect fluvial forms, vegetation and sediment transport dynamics at different spatio-temporal scales. These data allow to detect present river trajectories and to explore alternative paths more appropriate for a specific river morphology.

Exploiting the greater availability of remote sensing data, this study investigated the spatio-temporal dynamics of vegetation and sediment within the bankfull stream over the last 15 years. The study sites are several reaches of Oglio River, characterized by different morphological elements. Using an automatic procedure that combines image segmentation and classification algorithms, we identified the evolution of sediment bars/islands, the vegetation dynamics (distinguishing pioneer and mature stands) and the consequences of human and natural disturbances (morphological change after flood event, vegetation harvest, impacts of soil bioengineering work or construction of bank protection). The results clearly show, over the sediment islands, how the pioneer species occupy the empty spaces within the first 5 years and reach a vegetation stability only after 9-12 years. Based on such spatio-temporal dynamics, we can plan the management practice on the riparian vegetation indicating both timing- intensity and economic costs over time.

References

1. Hervé Piégay, (...), Louise Slater, 2020, Remotely sensed rivers in the Anthropocene: state of the art and prospects. *Earth Surf. Process. Landforms*, 45, 157–188
2. Vittoria Scorpio, (...), Francesco Comiti, 2020. Restoring a glacier-fed river: Past and present morphodynamics of a degraded channel in the Italian Alps. *Earth Surf. Process. Landforms*, 45, 2804-2823.



Reference topic: remote sensing, irrigation, Sentinel-2
Presentation type: oral

Early recognition of irrigated areas using Sentinel-2 data in Central Italy

Lorenzo Vergni^{1*}, Marco Vizzari¹, Alessandra Vinci¹, Francesco Santaga¹, Francesca Todisco¹

¹*Department of Agricultural, Food and Environmental Science, University of Perugia, Borgo XX Giugno 74, 06124, Perugia, Italy (corresponding: lorenzo.vergni@unipg.it)*

The large-scale recognition of irrigated areas, based on remote-sensing data, is extremely useful information for water resources planning and management. In this work, the time series of three optical indices derived from Sentinel-2 (S2) data were analyzed to classify 92 areas (34 non-irrigated and 58 irrigated) in the period 2017-2019 in Central Italy. The indices considered are the Normalized Difference Vegetation Index (NDVI), the Modified Soil-Adjusted Vegetation Index (MSAVI2), and the Normalized Difference Moisture Index (NDMI). Two different techniques were tested in the classification, based respectively on Random Forest (RF) and Dynamic Time Warping (DTW). The overall accuracy (OA) of the classification was assessed gradually increasing the number of S2 observations from the beginning of the irrigation season (May 15), thus allowing to evaluate how early a sufficiently reliable recognition is obtained. The results show that NDVI and MSAVI (both based on the near-infrared wavelengths) are usually more accurate than NDMI (based on the shortwave infrared). The two classification algorithms have very similar OA values (about 90%) when applied to the entire series of observations available at the end of the season. Instead, early recognition occurs more effectively with the RF technique than with DTW. For RF we get OA values close to 90% as early as mid-July (2 months of data), whilst DTW reaches the maximum accuracy starting from mid-August (3 months of data).

References

1. Benincasa P, Antognelli S, Brunetti L, Fabbri CA, Natale A, Sartoretti V, Modeo G, Guiducci M, Tei F, Vizzari M (2017). Reliability of NDVI derived by high resolution satellite and UAV compared to in-field methods for the evaluation of early crop N status and grain yield in wheat. *Exp Agric*, 1-19.
2. Vizzari M., Santaga F, Benincasa P (2019). Sentinel 2-based nitrogen VRT fertilization in wheat: Comparison between traditional and simple precision practices. *Agronomy*, 9, 278.
3. Vergni L, Todisco F, Di Lena B, Mannocchi F (2020). Bivariate analysis of drought duration and severity for irrigation planning. *Agricultural Water Management*, 229, 105926.



ASSOCIAZIONE ITALIANA
DI INGEGNERIA AGRARIA



Dipartimento Territorio
e Sistemi Agro-Forestali
Università di Padova

Reference topic: remote sensing, soil moisture, Unmanned Aerial Systems

Presentation type: oral

Soil Moisture Retrievals from Unmanned Aerial Systems (UAS)

Nunzio Romano¹, Ruodan Zhuang^{2*}, Salvatore Manfreda³, Silvano Fortunato Dal Sasso², Carolina Allocca¹, Paolo Nasta¹

¹ Department of Agricultural Sciences, AFBE Division, University of Naples Federico II, Portici, Via Università 100, 80055, Portici (NA), Italy (paolo.nasta@unina.it, carolina.allocca@unina.it, nunzio.romano@unina.it)

² Department of European and Mediterranean Cultures, Architecture, Environment, Cultural Heritage, University of Basilicata, Via Lanera 20, 75100 Matera (MT), Italy (ruodan.zhuang@unibas.it, silvano.dalsasso@unibas.it)

³ Department of Civil, Architectural and Environmental Engineering, Università degli Studi di Napoli Federico II, Via Claudio 21, 80125 Napoli (NA), Italy (salvatore.manfreda@unina.it)

Spatial and temporal dynamics of soil moisture is vital for water resources management. Unmanned Aerial Systems (UAS) offer a great potential in monitoring this variable at sub-meter level and at relatively lowcost. In this research, UAS-based soil moisture products have been tested using different algorithms: 1) thermal inertia; 2) random forest regression; and 3) temperature–vegetation trapezoidal model. The thermal inertia model, which builds upon the dependence of the thermal diffusion on soil moisture, requires the soil thermal inertia estimation that is quantified by processing visible and near infrared and thermal infrared images acquired at two different times of a day. The random forest regression model is used to downscale gridded soil moisture from 1km to 15cm grid size by applying UAS data and Digital Elevation Model (DEM) information. Finally, the temperature–vegetation trapezoidal model is used to map soil moisture over vegetated pixels. The comparison of the three algorithms helps to identify the advantages and disadvantages of each procedure for retrieving soil moisture with UAS. As a case study, a typical cropland area called MFC2 (about 8 ha) covered by olive, cherry and walnut trees in southern Italy, is used, where optical and thermal images and in-situ data were simultaneously acquired. MFC2 belongs to the Alento hydrological observatory, where long-term studies on vadose zone hydrology have been conducted across a range of spatial scales. Our findings provide a contribution towards improving our knowledge on evaluating the ability of UAS to map soil moisture.

References

1. Tmušić, G., Manfreda, S., Aasen, H., James, M.R., Gonçalves, G., Ben-Dor, E., Brook, A., Polinova, M., Arranz, J.J., Mészáros, J., et al. 2020. Current practices in UAS-based environmental monitoring. *Remote Sensing* 12, 1001.
2. Zhuang, R., Zeng, Y., Manfreda, S., Su, Z., 2020. Quantifying Long-Term Land Surface and Root Zone Soil Moisture over Tibetan Plateau. *Remote Sensing*, 12, 509.
3. Paruta, A., Ciraolo, G., Capodici, F., Manfreda, S., Dal Sasso S.F., Romano, N., Nasta, P., Ben-dor, E., Francos, N., et al., 2020. A geostatistical approach to map near - surface soil moisture through hyper - spatial resolution thermal inertia. *IEEE Trans. Geosci. Remote Sens.* 1-18.